



# LONKING 龙工

Code: 10801632670

## CDM932NG WHEEL LOADER

Efficiency Rules the Future



Product VR



### TECHNICAL PARAMETERS

BASIC	Bucket Capacity	0.8 m <sup>3</sup>
	Rated Payload	1500kg
	Operating Weight	5230kg
	Traction Force	52kN
	Breakout Force	35kN
	L×W×H	5925×2100×2950mm
ENGINE	Manufacturer/Model	YUNNEI/YN38GBZ1 ( Nation II )
	Rated Power	65kW/2400rpm
	Rated Torque	285N·m/1600-1800rpm
DRIVE TRAIN	Transmission Type	Countershaft Powershift
	Shift Type	Fixed Shaft Hydraulic Shift Spur Gear
	Pressure of Transmission	1.1-1.5MPa
	Gear	2F/2R
	Torque Converter	Single-stage, Single-turbine, 3-element
	Torque Ratio	3.13
	Main Reducer	Spiral Bevel Gear Single-stage Reduction
	Final Reducer	Planetary Reduction
	Tire	16/70-20
	Travel speed-Forward	8/20km/h
Travel speed-Reverse	8/20km/h	
BRAKE SYSTEM	Service Brake	Air Drive, Four Wheel Brake (Dry)
	Setting Pressure	0.78MPa
	Parking Brake	Flexible Shaft Controlled Caliper
STEERING SYSTEM	Type	Hydraulic Load Sensor System
	Steering Pump	Shared With Working Pump
	System Pressure	14Mpa
HYDRAULIC SYSTEM	Steering Angle	±30°
	Type	Pilot control
	Working Pump	Gear Pump
	Flow Rate	120L/min-2400rpm
	Control Valve	2 Spool
ELECTRIC SYSTEM	System Pressure	16MPa
	Cycle Time (Sec)	8.2
	System Voltage	24V
SERVICE REFILL CAPACITY	Battery ( 2 in series)	2x80 Ah
	Fuel Tank	90L
	Hydraulic Tank	65L
	Transmission	19L
	Front Axle / Rear Axle	24L

### CONFIGURATION

YUNNEI Engine
LONKING Transmission
LONKING Torque Converter
LONKING Drive Axle
Pilot control Working System
High Dump
Air Conditioner

### OPTIONAL

Bucket(1.2m <sup>3</sup> , width2.1m , 3 Piece Cutting Edges)
Bucket(1.2m <sup>3</sup> , width2.1m , Five Detachable Teeth)
3rd Spool for Auxiliary Function
Hydraulic Quick Hitch
Quick Hitch Bucket ( 3 Piece Cutting Edges )
Quick Hitch Log Fork
Mechanical Quick Hitch
Copper Slag Grapple
Log Fork
Warm Air Blower
Air prefilter

For more information on Lonking products,  
Please contact our local agent:

The following blank can be used for notes or comments.

Lonking, Lonking CDM Series and their respective logos, as well as corporate identity in this leaflet are trademarks of Lonking Holdings Ltd., and may not be used without written permission. 2020/03

Specifications and design are subject to change without prior notice. Machines shown may not include optional accessories.

LONKING (FUJIAN) INTERNATIONAL TRADE CO.,LTD.  
**LONKING HOLDINGS LIMITED**  
Add:26 Minyi Road,Xinqiao,Songjiang Industrial Zone,Shanghai  
Tel: +86-21-3760 2242 E-mail:export@lonking.cn  
<http://www.lonkinggroup.com>

- RATED POWER: 65kW/2400rpm
- BUCKET CAPACITY: 0.8m<sup>3</sup>
- RATED PAYLOAD: 1500kg
- OPERATING WEIGHT: 5230kg